


Datasheet

Art.No. 57.510.9055.0

Earth terminal WKN 10 SL / U / V0

Ground DIN rail terminal block with screw connection for mounting on TS 35, nominal cross section 10 mm², width 10 mm, color green/yellow



Art.No.	57.510.9055.0
EAN	4015573500129
Order unit	50 pieces

Approvals



Technical data

General

Nominal cross section	10 mm²
Colour	Green/yellow
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	10 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	No

Technical data

Rated voltage	800 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	No
Type of insulation material	Thermoplastic
Length	54 mm

Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section solid	1.5 mm²

Maximum cross section solid	10 mm ²
Minimum cross section fine stranded	2.5 mm ²
Maximum cross section fine stranded	10 mm ²
Minimum cross section stranded	16 mm ²
Maximum cross section stranded	16 mm ²
Wire strip length	13 mm
Torque conductor mounting	2 Nm
Torque rail mounting	1,2

Technical Data UL/CSA

Cross section UL	16-6 AWG
Cross section CSA	16-6 AWG

Classification

ECLASS 8.1	27141141: Ground terminal block
ETIM 5.0	EC000901: Ground terminal block
ETIM 4.0	EC000901: Ground terminal block
ETIM 3.0	EC000901: Ground terminal block