

Device Profile

Customer Support : 0931352970
Supplies Number :
Customer Asset Tag Number :
Xerox Asset Tag Number :
Machine Serial Number : 3560642791

Installed Options

Network Card : Present
DADF : Present
HDD : Present
Finisher : Not present
Fax Card : Present
Embedded Fax : Installed/Enabled
Server Fax : Not Installed/Disabled
Email : Installed/Disabled
Network Scan : Not Installed/Disabled
Network Accounting : Not Installed/Disabled
Disk Overwrite : Not Installed/Disabled
Job Overwrite : Not Installed/Disabled
Memory Size : 256 Mbytes
HDD Size : 40.00 Gbytes

Printer Setup

System Software Version : 10.100.46.000
Main Controller : 1.01.04.38
Image Output Terminal : 1.00.28
User Interface : 0.030.29.015
Network Controller : 2.01.13
Document Feeder : 1.02
Finisher Version : Not Installed
Tray 2 Firmware : Not Installed
Tray 3 Firmware : Not Installed
Tray 4 Firmware : Not Installed
PCL5E Version : PCL5e 5.91 02-10-2009
PCLXL Version : PCL6 5.90 02-03-2009
PS Version : PS3 V1.94.06 12-22-2008
TIFF Version : TIFF 0.70.00 07-10-2006
PDF Version : PDF V1.00.39 10-17-2006
IH Version : 0.00.01
Power Saver : 60 minutes
Startup Config Report Enabled : Enabled
Error Sheets Enabled : Disabled
Banner Sheets Enabled : Disabled

Network Setup

NetWare Settings

NetWare Enabled : : Disable
Printer Server Name : XRX_0000AA963E05
NDS Tree : XEROX_DS_TREE
NDS Context : O=XEROX_DS_CONTEXT
Novell Filing Transport : IPX
IPX Frame Type : Auto
Poll Interval : 5
SAP Rate : 60
Primary File Bindery Server :

TCP/IP Settings

TCP/IP Enabled : Enable
Host Name : XRX_0000AA963E05
IP Address : 192.168.174.249
SubNet Mask : 255.255.255.0
Default Gateway : 192.168.174.254
Automatic Addressing : STATIC
LPD Enabled : Enable
LPD Port Number : 515
Raw TCP/IP Printing Enabled : Enable
Raw TCP/IP Printing Port Number : 9100
IPv6 : Disabled
Host Name :
Link-Local Address :

DNS Setting

Domain Name : kanzleijeske.de
Primary DNS Server : 192.168.174.1
Alternate DNS Server 1 : 0.0.0.0
Alternate DNS Server 2 : 0.0.0.0
Dynamic DNS Enabled : Enable

SLP Setting

SLP Enabled : Enable
Version : 2
Port Number : 427
Character Set : US-ASCII
Directory Agent :

Network Setup(cont.)

Scope 1 :
Scope 2 :
Scope 3 :
Message Type : MULTICAST
Multicast Radius : 255
MTU : 1400

AppleTalk Setting

AppleTalk Enabled : Disabled
Name : XRX_0000AA963E05
Zone : *

Printer Type : LaserWriter

HTTP Setting

HTTP Enabled : Enabled
Port Number : 80
Max Connections : 32

Web Services

Scan Template Management : Disabled

Port Setup

Ethernet Profile

Ethernet Card : PCI Card
MAC Address : 00:00:AA:96:3E:05
Speed : Auto

Network Scanning Setup

Network Scanning Enabled : Enabled
Confirmation Sheet Enabled : Enabled

Network Scanning (Default Repository)

Protocol :
Server Name :
Path :
Login Name :

Network Scanning (Template Pool)

Protocol :
Server Name :
Path :
Login Name :

Network Scanning (Alternate Repository 1)

Protocol :
Server Name :
Path :
Login Name :

Network Scanning (Alternate Repository 2)

Protocol :
Server Name :
Path :
Login Name :

Network Scanning (Alternate Repository 3)

Protocol :
Server Name :
Path :
Login Name :

Network Scanning (Alternate Repository 4)

Protocol :
Server Name :
Path :
Login Name :

Server Fax Setup

Server Fax Enabled : Disabled

Fax Forward Setup

Fax forward to Fax number : Disabled

Media Trays

Media Name : Tray 1
Paper Type : Plain Paper
Paper Color : White
Paper Size : 8.5 x 14"
Media Name : MP Tray
Paper Type : Plain Paper
Paper Color : White
Paper Size : A4

Network Authentication Setup

Kerberos

Default Realm :
Default Address :
Alternate1 Realm :
Alternate1 Address :
Alternate2 Realm :

Network Authentication Setup(cont.)

Alternate2 Address :

Backup2 Address :

Server Message Block (SMB)

NT Domain :

Backup Domain :

Alternate1 Domain :

Alternate2 Domain :

Alternate3 Domain :

Alternate4 Domain :

Alternate5 Domain :

Alternate6 Domain :

Accounting Setup

Accounting Mode : Disabled

Authentication Mode : Disabled